

# EQUIPEMENTS D'EMBALLAGES SATURN

6055 CH. ST-FRANCOIS, ST-LAURENT, QUEBEC PACKAGING EQUIPMENT

CANADA H4S 1B6

TEL: 514-956-1603 FAX: 514-956-8124

WEB: WWW.SATURNPACKAGING.COM

EQUIPEMENTS D'EMBALLAGE



PACKAGING EQUIPMENT

## OMEGA SERIES:

### General features

Alloy aluminum sealing head.  
Auto safety shutdown.  
Scrap winder.  
Cycle counter.  
P. L. C. controle unit.  
Film miser.  
Power film unwind, right angle inverting head.  
Pin perforator rollers.  
Vertical & horizontal photo eyes.  
Anti-static treatment unit.  
Automatic infeed conveyor.  
Automatic outfeed conveyor.  
High versatility, easy to adjust, for varied products.  
Console legs on casters, with adjustable height levelers

### Caracteristiques generales

Machoire de scellage en aluminium.  
Arret d'urgence automatique.  
Bobineur de rebut de pellicule motorise.  
Compteur de cycles.  
Unite de controle electronique, P. L. C.  
Rouleaux guide a pellicule.  
Debobineur de pellicule motor & tete d' inversion a 90 D.  
Rouleaux perforateur.  
Photo cell. horizontale & verticale.  
Traitement anti-statique.  
Convoyeur d'entrée motorise.  
Convoyeur de sortie motorise.  
Facile a ajuster pour differents produits.  
Sur console et roulettes & levier a hauteur ajustable.

### SPECIFICATION

Description	OMEGA (ALS 1.0) 1820	Description
Voltage	220v 50/60Hz	Voltage
Amperage	15 Amps 1 PH	Amperage
Sealing area	18"x 20"	Dimensions de scellage
Max. product size not combined	15"Wx 19"Lx 4"H	Dimensions max. du produit non combine
Floor space	67"Lx 34"Wx 55"H	Espace sur plancher
Maximum jaw opening height	5"	Ouverture de machoir
Air pressure	80 PSI	Pression d'air
Packages/ minute	Up to/ jusqu'a 25	Paquets/ minute
Warranty	15 Months / Mois	Garantie

### OPTIONS

Description	Omegaline	Description
Flexi glass cover on sealing head	ALS-O-01	Couvert en plexi glass sur machoires
Closing conveyor for small products	ALS-O-02	Convoyeur de transfer pour petits produits
Tunnel model kappa KT3.5E (18"Wx 40"Lx 7"H)	KT3.5E	Tunnel model kappa KT3.5E (18" LR x40" LG x7"H)
Variable speed infeed conveyor (16" Wx 72" L)	CON-7216-M	Convoyeur d'entrée motorise a vitesse variable (16"LRx72"LG)
Gravity extension exit conveyor (15"Wx 72" L)	CON 90D15R1.5E2	Convoyeur a gravite 90 DG (15"Lx 1.5" DIA R.x 2"c.c.)
P. V. C. rollers	PVC-R	Rouleaux en P. V. C.

