

EQUIPEMENTS D'EMBALLAGES SATURN

6055 CH. ST-FRANCOIS, ST-LAURENT, QUEBEC PACKAGING EQUIPMENT

CANADA H4S 1B6

TEL: 514-956-1603 FAX: 514-956-8124

WEB: WWW.SATURNPACKAGING.COM



STARPAK SERIES:

General features

Top bottom and side heater air flow.
 High velocity twin blowers.
 Adjustable sealing platform.
 Adjustable film cradle.
 Adjustable stainless steel loading table.
 Speed controlled tunnel conveyor teflon mesh belt.
 Baked paint epoxy finished F. D. A.
 Microprocessor controlled impulse sealing system.
 Fully upgradable add-on options.
 Pin perforator roller with brake.
 Magnet kit.
 Easy move forward and or backward (sealer) to center product into tunnel.
 Precision height adjustable take-away conveyor kit.
 Hand crank tunnel elevator to align with sealer.

 Heavy duty unitized floor stand on casters & brakes.
 Complete digital display & elec. Control & keypad.
 Automatic cooldown circuit for shutdown procedure.

Caracteristiques generales

Circulation d'air chaud du haut, bas et cote.
 Double souffleur a haute velocite.
 Table de travail ajustable.
 Support de pellicule ajustable.
 Table de chargement en acier inox. Ajustable.
 Convoyeur du tunnel a vitesse variable fillet en teflon.
 Peinture cuite finie epoxy F. D. A.
 Controle par systeme d'impulsion microprocesseur.
 Concept modulaire, Options faciles a ajuster.
 Rouleaux perforateur a freins.
 Engagement electromagnetique.
 Ajustement facile du mouvement avant/arriere pour aligner produit horizontalement au centre du tunnel.
 Convoyeur de transfert motorise, a hauteur ajustable.
 Tunnel a hauteur ajustable pour aligner produit verticalement a la scelleuse.
 Console robuste avec roulettes a freins.
 Controle complet digital & electronique.
 Arret automatique.

SPECIFICATIONS

Description	STARPACK	Description
Voltage	220V or 220/110V 50/60HZ	Voltage
Amperage	20 Amps 1PH	Amperage
Sealing area	16" x 20"	Dimensions de scellage
Tunnel chamber	17"x 9"x 27"	Chambre du tunnel
Heating elements	4400 watts	Elements
Floor space	7'x 2'1/2	Espace sur plancher
Weight	550 lbs	Poids
Film capacity	21"	Capacite de pellicule
Tunnel conv. Speed	45 F.P.M/13.5 M.P.M.	Vitesse conv. Tunnel
Packages/ Minute	14-20	Paquets/Minute
Warrantie	One yr(10yrs,30mths)	Garantie

OPTIONS

Description	Item	Description
Film clamps	OU-01	Pince a pellicule
Loading via air jet table	OU-02	Table a chargement via jet d'air
Heat protection plate on tunnel	OU-03	Plaque de protection de chaleur pour tunnel
power film unwind right angle with inverting head film	OU-06	Debobineur a angle motorise a tete d'inversion
12" High tunnel opening	OU-09	Ouverture de tunnel de (30cm) de haut
Pneumatic system	OU-20	Systeme pneumatique

