

# ERGO WORK POSITIONERS

1,000/2,000/3,000 LBS



## STRADDLE ERGO WORK POSITIONER

MODEL NO.	CAPACITY (LBS.)	LIFT HEIGHT (IN.)	LOW'D FORK HEIGHT (IN.)	FORK WIDTH (IN.)	FORK LENGTH (IN.)	STRADDLE I.D. (IN.)	SHIPPING WEIGHT (LBS.)
SEWP36-10	1,000	36	3 1/4	26 1/2	42	50	600
SEWP36-20	2,000	36	3 1/4	26 1/2	42	50	650
SEWP36-30	3,000	36	3 1/4	26 1/2	42	50	675
SEWP48-10	1,000	48	3 1/4	26 1/2	42	50	625
SEWP48-20	2,000	48	3 1/4	26 1/2	42	50	675
SEWP48-30	3,000	48	3 1/4	26 1/2	42	50	700
SEWP60-10	1,000	60	3 1/4	26 1/2	42	50	650
SEWP60-20	2,000	60	3 1/4	26 1/2	42	50	675
SEWP60-30	3,000	60	3 1/4	26 1/2	42	50	725



## ERGO WORK POSITIONER

MODEL NO.	CAPACITY (LBS.)	LIFT HEIGHT (IN.)	LOW'D FORK HEIGHT (IN.)	FORK WIDTH (IN.)	FORK LENGTH (IN.)	SHIPPING WEIGHT (LBS.)
EWP36-10	1,000	36	3 1/4	26 1/2	42	600
EWP36-20	2,000	36	3 1/4	26 1/2	42	650
EWP36-30	3,000	36	3 1/4	26 1/2	42	675
EWP48-10	1,000	48	3 1/4	26 1/2	42	625
EWP48-20	2,000	48	3 1/4	26 1/2	42	675
EWP48-30	3,000	48	3 1/4	26 1/2	42	700
EWP60-10	1,000	60	3 1/4	26 1/2	42	650
EWP60-20	2,000	60	3 1/4	26 1/2	42	675
EWP60-30	3,000	60	3 1/4	26 1/2	42	725

### CAPACITY

- 1,000/2,000/3,000 lbs.

### LIFT HEIGHT

- 36" / 48" / 60"

### LOWERED HEIGHT

- 3 1/4" (see specs)

### SAFETY

- Velocity fuse on each cylinder
- Floor lock

### POWER SUPPLIES

- D/C 12 volt battery with joy stick activation and a built in 12 volt charger (standard)
- A/C 110 volt Hand held pendant (optional)

### OPTIONS

- Different straddle leg sizes
- Different fork width lengths and heights
- D/C battery powered with hand held pendant
- Slip-on platforms