

# FOX C3 / C4 SEMI AUTOMATIC



## OPTIONS

- Ramp (FOX C3)
- Heavy duty ramp for electric powered hand truck (FOX C3)
- Ramp extension (FOX C3)
- Tower height extension
- Base extension
- Roping bar (FOX C4)
- Scale package
- Automatic end of cycle film cut off
- Dual turntable (FOX C3-C4)
- Top platen (FOX C3-C4)

\* colors may not be exactly as shown

## CONTROL FEATURES

- ✓ • Programmable Key Pad Controls
- ✓ • LCD Display Screen (providing function control viewing)
  - Variable Turntable Speed 0-15 RPM
- ✓ • Variable Film Carriage Speed Up/Down Control
- ✓ • Separate Top/Bottom Wrap Selectors 1-9
- ✓ • Separate Film Height Selector 1-9"
  - Flush Mounted Control Panel (built into tower)
  - Cycle Counter
  - Manual Carriage Raise/Lower Control
  - Turntable Jog with Auto Home Alignment
  - Large Emergency push button power On / Off Switch with indicator light
  - Start Cycle Push Button
  - Standard Wrap Up/Down Program
  - 12 Volt DC Control System (for operator safety)
  - All circuits protected by fuses (easy access)
  - 20 amp Power Board Circuits to carry a 10 amp load

## TECHNICAL INFORMATION

- All switches, relays, SCR controls are available locally throughout North America
- Power Requirements: 115 VAC @ 15 Amps, 60 Hz
- Complete manual with electrical schematic provided with machine

## TURNTABLE DRIVE

- Positive home alignment
- 0 -15 RPM turntable speed
- 1/2 HP SCR variable speed drive
- Adjustable electronic soft start / stop

## STRUCTURAL FEATURES

- ✓ • Heavy Duty 3/8" turntable plate
- Fork Lift portable from front or rear
- Large formed steel tower
- 5/16" thick base plate
- Rigid unibody base frame construction

## CARRIAGE LIFT

- V Groove wheel supports providing effortless movement and maximum stability (Qty4)
- Heavy duty ANSI #50 chain carriage lift
- 1/2 HP DC SCR variable speed drive
- ✓ • Carriage chain fully guarded

## FILM DELIVERY

- ✓ • FOX "Linear" 20 inch powered pre-stretch film delivery system
  - Easy thread film carriage
  - No hinges, latches or idler rollers to wear and cause inconsistent film stretching
  - Electronic film force control on film carriage
  - Adjustable mechanical force to load
  - Sensor switch film feed speed control
  - 1/2 HP DC SCR variable speed film drive
- ✓ • Pre-stretch 50-300% upon request (200% standard settings)
  - Triple beam auto height eye capable of recognizing all colors including black

## FOX C3

- Rigid base frame construction
- 56" Diameter steel turntable plate
- ✓ • 32 table support wheels requires no lubrication to the face or under the table (250 lbs dynamic each wheel)
- Heavy duty #50 chain and sprocket drive system
- 3" from floor to top of turntable
- Suggested Maximum Load Size: 55"L x 55" W (78" Diagonal) x 90" H
- ✓ • Weight Capacity: 5000 lbs.

## FOX C4

- Rigid base frame construction
- 48" octagon steel turntable plate
- No face lubrication required
- Lubrication points on caster roller bearings and swivel
- ✓ • 4 Heavy Duty Support Swivel Casters (2000 lbs each)
- Heavy duty #50 chain and sprocket drive system
- 10 7/8" from floor to top of turntable
- Suggested Maximum Load Size: 55"L x 55" W (78" Diagonal) x 82" H
- ✓ • Weight Capacity: 5000 lbs.